

PR series

■ STANDARD RATINGS

VDC (SV)	Cap (μF)	Size DxL(mm)	ESR (mΩ, 20°C, 100kHz) (max.)	Rated ripple current (mA rms/105°C, 100kHz)	Leakage Current (μA)(max.)	Part Number
2.5 (2.9)	560	6.3×8	12	2000	500	SPR0EM561E08000RAXXX
	680	6.3×8	12	2000	500	SPR0EM681E08000RAXXX
	820	6.3×9	12	2000	500	SPR0EM821E09000RAXXX
	1200	8×9	14	2100	600	SPR0EM122F09000RAXXX
6.3 (7.2)	330	6.3×8	12	1900	500	SPR0JM331E08000RAXXX
	470	6.3×8	12	1900	592	SPR0JM471E08000RAXXX
		8×9	14	2100	592	SPR0JM471F09000RAXXX
	560	6.3×8	12	1900	706	SPR0JM561E08000RAXXX
	680	8×11	12	2200	857	SPR0JM681F11000RAXXX
	820	8×11	12	2200	1033	SPR0JM821F11000RAXXX
	1000	8×11	12	2300	1260	SPR0JM102F11000RAXXX
	1200	8×11	12	2300	1512	SPR0JM122F11000RAXXX
1500	10×12	12	2500	1890	SPR0JM152G12000RAXXX	
10 (11.5)	220	6.3×8	12	1700	500	SPR1AM221E08000RAXXX
	270	6.3×8	12	1700	540	SPR1AM271E08000RAXXX
	330	6.3×10	12	1800	660	SPR1AM331E10000RAXXX
	470	8×11	12	2000	940	SPR1AM471F11000RAXXX
	560	8×11	12	2000	1120	SPR1AM561F11000RAXXX
	680	8×11	12	2100	1360	SPR1AM681F11000RAXXX
	820	8×11	12	2100	1640	SPR1AM821F11000RAXXX
	1000	10×12	12	2200	2000	SPR1AM102G12000RAXXX
	1200	10×12	12	2200	2400	SPR1AM122G12000RAXXX
	1500	10×12	12	2400	3000	SPR1AM152G12000RAXXX
16 (18.4)	100	6.3×8	17	1500	500	SPR1CM101E08000RAXXX
	180	6.3×8	17	1500	576	SPR1CM181E08000RAXXX
	220	6.3×10	17	1600	704	SPR1CM221E10000RAXXX
	270	8×11	14	1700	864	SPR1CM271F11000RAXXX
	330	6.3×10	14	1600	1056	SPR1CM331E10000RAXXX
	470	8×11	14	1700	1504	SPR1CM471F11000RAXXX
	560	10×12	14	2000	1792	SPR1CM561G12000RAXXX
	680	10×12	14	2000	2176	SPR1CM681G12000RAXXX
	820	10×12	14	2100	2624	SPR1CM821G12000RAXXX
	1000	10×12	14	2100	3200	SPR1CM102G12000RAXXX
25 (28.8)	68	6.3×7	24	1300	500	SPR1EM680E07000RAXXX
	82	6.3×7	24	1300	500	SPR1EM820E07000RAXXX
		6.3×8	24	1300	500	SPR1EM101E08000RAXXX
	100	8×11	22	1500	500	SPR1EM101F11000RAXXX
	120	6.3×10	22	1400	600	SPR1EM121E10000RAXXX
	180	8×9	24	1300	900	SPR1EM181F09000RAXXX
	220	8×11	22	1500	1100	SPR1EM221F11000RAXXX
		10×12	22	1700	1100	SPR1EM221G12000RAXXX
	270	8×11	22	1500	1350	SPR1EM271F11000RAXXX
	330	10×12	22	1700	1650	SPR1EM331G12000RAXXX
	470	8×16	22	1700	2350	SPR1EM471F16000RAXXX
		10×12	22	1800	2350	SPR1EM471G12000RAXXX
560	10×12	22	1800	2800	SPR1EM561G12000RAXXX	
35 (40.3)	47	6.3×7	52	1100	500	SPR1VM470E07000RAXXX
	56	6.3×7	52	1100	500	SPR1VM560E07000RAXXX
	68	6.3×7	52	1100	500	SPR1VM680E07000RAXXX
	82	6.3×7	52	1100	574	SPR1VM820E07000RAXXX
	100	6.3×10	42	1200	700	SPR1VM101E10000RAXXX
	150	10×12	32	1400	1050	SPR1VM151G12000RAXXX
		8×11	32	1300	1540	SPR1VM221F11000RAXXX
	220	10×12	32	1400	1540	SPR1VM221G12000RAXXX
	270	10×12	32	1400	1890	SPR1VM271G12000RAXXX
	330	10×12	32	1400	2310	SPR1VM331G12000RAXXX

Conductive Polymer Radial Type